

Caractéristiques techniques
Nouvelle SEAT Leon ST



	1.0 TSI 115 CH	1.0 TSI 115 CH DSG	1.2 TSI 86 CH	1.2 TSI 110 CH
MOTEUR				
Nombre cylindres / Soupapes	3 Cyl. - 12v		4 Cyl. - 16v	
Cylindrée	999		1197	
Alésage / Course (mm)	74,5x76,4		71x75,6	
Taux de Compression	10,5			
Puissance maximale (kW/HP/rpm)	85/115/5000-5500		63/86/4300-5300	81/110/4600-5600
Couple Max (NM/rpm)	200/2000-3500		160/1400-3500	175/1400-4000
Alimentation	TSI - Direct Injection			
Allumage	Electronic map-controlled ignition			
Type de carburant	ROZ 95			
Normes d'émission	EU6			
Alternateur (A)	140		110-140	
Batterie (Ah)	59-69/320-360	69/360	44-51-61/220-280-330	59-69/320-360
PERFORMANCE				
Vitesse maximale	198	202	178	194
Accélération 0-100 km/h (s)	9,8		12,1	10,1
CO2				
Cycle Mixte	102		119	114
Consommation				
Circuit Mixte	4,4		5,1	4,9
TRANSMISSION				
Boîte de vitesse	Manual 6-speed Start-Stop Ecomotive	DSG 7-speed Start-Stop Ecomotive	Manual 5-speed	Manual 6-speed Start-Stop
I	3,769	3,765	3,769	3,615
II	1,955	2,273	1,955	1,947
III	1,281	1,531	1,281	1,281
IV	0,973	1,122	0,881	0,973
V	0,778	1,176	0,673	0,778
VI	0,642	0,951	-	0,646
R	-	-	-	-
Ratio groupe	3,182	4,167	3,182	3,182
Group ratio 1	4,056	4,438	3,933	4,056
CHASSIS				
Suspension avant	Independent type McPherson - coil springs - hydraulic shock absorber			
Suspension arrière	Semirigid axle - coil springs - hydraulic shock absorber			
Direction	R-EPS (Rack Electric Power System)			
Angle de braquage	10,3			
Système de freinage	Dual hydraulic circuit and brakes system diagonal split with brake booster			
Type freinage avant / arrière	Front Ventilated Disc / Solid Disc Brake			
Freins avant (mm)	276x24			
Freins Arrière (mm)	253 x 10			
Jantes (")	15" - 16"		15" - 16" - 17"	
Pneus	195/65 R15 - 205/55 R16		195/65 R15 - 205/55 R16 - 225/45 R17	
CARROSSERIE				
Type de corps	5 D			
Longueur/largeur/hauteur (mm)	Reference, Style and X-Cellence: 4249/1816/1454; FR: 4548/1816/1439			
Empattement (mm)	Reference, Style and X-Cellence: 2636; FR: 2634			
Fvoies avant et arrière (mm)	1549/1520 (R15"); 1544/1514 (R16"); 1538/1508 (R17"); 1534/1511 (R18") [FR: 1538/1512 (17"); 1534/1511 (18")]			
Capacité du coffre	587			
Capacité du réservoir (L)	50			
POIDS				
Poids en ordre de marche avec chauffeur (kg)	1236	1259	1233	1247
Poids maximum autorisé (kg)	1770		1800	
Poids de remorquage max. frein 12% (Kg)	1000	1100	1100	1300